



NAME OF YACHT: \_\_\_\_\_

HULL NUMBER: \_\_\_\_\_

## STANDARD INSPECTION LIST

### CATEGORY 4

#### BELOW DECK

RULE	ITEM TO CHECK	Answer Yes/No
3.23.5 (b)	<b>1 manual bilge pump</b>	
3.23.5 (f)	<b>2 buckets of stout construction</b> of at least 9 liters, <b>with lanyard</b>	
3.29.1 e)	<b>A hand-held marine VHF transceiver, watertight or with a watertight cover.</b>	
3.29.1 f)	<b>Radio receiver</b> capable of receiving weather bulletins (Recommended)	
4.03	Soft wood <b>plugs</b> tapered and attached to the appropriate fitting	
4.05	At least two <b>fire extinguishers</b> readily accessible in suitable and different parts of boat	
4.06.1	<b>1 anchor</b> readily accessible	
4.07.1 a) 4.23.2 a)	<b>Flashlight</b> watertight. Spare batteries and bulbs	
4.08.1	<b>First aid kit</b> and manual	
4.09	<b>Fog horn</b>	
4.10	<b>Radar reflector.</b> If octahedral, diagonal not less than 456 mm.	
4.16	<b>Tools and spare parts.</b> Means to disconnect or sever the standing rigging	
4.17	<b>Yacht's name</b> on buoyant equipment (lifejackets, lifebuoys, etc.)	
4.18	<b>Retro-reflective material</b> on lifejackets, lifebuoys, liferafts and lifeslings	
4.23.2 b)	<b>Watertight, high-powered white spotlight (searchlight)</b> with spare batteries and bulbs	
4.26.4 c)	<b>Storm trysail</b> or mainsail reefing to reduce luff 40%	
5.01.1/5.01.2	<b>Lifejacket</b> for each crew member as per OSR 5.01.1 & .2	No:

#### ON CHART TABLE

RULE	ITEM TO CHECK	Answer Yes/No
	<b>Measurement certificate H8</b>	
3.24.1	<b>Compass deviations</b>	
4.10	<b>Radar reflector data</b> (10 m2 cross section if not octahedral)	
4.11	<b>Charts</b> (not solely electronic), light list and chart plotting equipment	
4.12	<b>Durable stowage chart</b> displayed where it can best be seen, clearly marked with the location of the principal items of safety equipment	

### ON DECK

RULE	ITEM TO CHECK	Answer Yes/No
3.14.2 a)	Lifelines required in Special Regulations shall be "taut". As a guide, when deflecting force of 50 N (5.1 kgf) is applied to a lifeline midway between supports, the lifelines shall not deflect more than 50 mm	
3.14.3	Complete <b>double lifeline</b> enclosure. Height according to table. Stanchions interval not less than 2.13 m. Upper rails of <b>bow pulpit</b> closed	
3.24.1 a)	<b>1 marine magnetic compass</b> , independent of any power supply, permanently installed and <b>adjusted</b>	
3.27.	Test <b>navigation lights</b> . Spare bulbs (see table). Height not less than upper lifeline	
4.22.1 a)	<b>Lifebuoy</b> with: drogue (or lifesling without drogue), self igniting light, retro-reflective and yacht's name within reach of helmsman and ready for instant use. When inflatable, shall be tested or serviced in accordance with its manufacturer's instructions	
4.24	<b>Heaving line</b> 15 m. minimum length, readily accessible to cockpit	

### PYROTECHNIC SIGNALS (Rule 4.23)

ITEM	EXPIRING DATE	CONDITION (G/F/P) (*)
4 RED HAND FLARES 4.23 Pyrotechnic signals	1	
	2	
	3	
	4	
2 ORANGE SMOKE 4.23 Pyrotechnic signals	1	
	2	

(\*): G (good), F (fair), P (poor)

Owner: \_\_\_\_\_

X-35, Hull No: \_\_\_\_\_

declares that he has checked all items of present list and they are as expressed above.

Signature: \_\_\_\_\_ Date: \_\_\_\_\_